





EYE-LCD-6000-QHD-LD

60-INCH 4K ULTRA-HD LCD MONITOR WITH DIRECT-LED BACKLIGHT



) FEATURES

- 60" Screen Diagonal (152 cm)
- Extra high resolution 3,840 × 2,160px
- Direct LED Backlight for best brightness uniformity and perfect colours
- Wide viewing angle
- High contrast
- Fast response time

) APPLICATION POSSIBILITIES


- eSignage applications
- Security control rooms, display of multiple camera signals in native resolution on one screen
- Detailed process controlling in high resolution
- Accurate diagnostic imaging in medical applications
- Digital post-production for broadcasting
- Designers / Design Engineers / Architects

) DIRECT LED BACKLIGHT

Previous LC displays with conventional CCFL backlight technology were likely to show a non-uniform brightness level over the entire screen. In order to achieve a uniform illumination of the entire screen, eyevis provides its new EYE-LCD-3150-QHD-LD with direct-LED backlight. Thanks to the new backlight illumination technology, the display provides very homogeneous images.

) LCD PANEL CONFIGURATION


Standard Panel Configuration: "Quadrant" Mode




) TECHNICAL SPECIFICATIONS

Resolution: 3840 × 2160 Pixels Active Screen Area: 1330.6 × 784.4 mm Brightness: 500 cd/m² (max.) Contrast: 5000:1 (typ.) Pixel Pitch: 0.3465 mm (H) × 0.3465 mm (V) Polariser: Anti Glare, Low Reflection, Hard Coating: 3H Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control Article Number: 17006		
Brightness: 500 cd/m² (max.) Contrast: 5000:1 (typ.) Pixel Pitch: 0.3465 mm (H) × 0.3465 mm (V) Polariser: Anti Glare, Low Reflection, Hard Coating: 3H Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Resolution:	3840 × 2160 Pixels
Contrast: 5000:1 (typ.) Pixel Pitch: 0.3465 mm (H) × 0.3465 mm (V) Polariser: Anti Glare, Low Reflection, Hard Coating: 3H Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Active Screen Area:	1330.6 × 784.4 mm
Pixel Pitch: 0.3465 mm (H) × 0.3465 mm (V) Polariser: Anti Glare, Low Reflection, Hard Coating: 3H Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Brightness:	500 cd/m² (max.)
Polariser: Anti Glare, Low Reflection, Hard Coating: 3H Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Contrast:	5000:1 (typ.)
Response Time: 6 ms Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 x DVI Single Link (optional 2 x DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 x 828.4 x 17.6 mm (WxHxD) Weight: approx. 75 kgs Accessory: IR Remote Control	Pixel Pitch:	0.3465 mm (H) × 0.3465 mm (V)
Colour Depth: 10 Bit Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Polariser:	Anti Glare, Low Reflection, Hard Coating: 3H
Frequency: 50/60 Hz Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Response Time:	6 ms
Viewing Angle: 176° / 176° Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Colour Depth:	10 Bit
Input Connection: 4 × DVI Single Link (optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Frequency:	50/60 Hz
(optional 2 × DVI Dual Link) Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Viewing Angle:	176° / 176 °
Backlight: Direct-LED Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control	Input Connection:	4 × DVI Single Link
Power Consumption: 360 Watt Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (W×H×D) Weight: approx. 75 kgs Accessory: IR Remote Control		(optional 2 × DVI Dual Link)
Outline Dimensions: 1410.4 × 828.4 × 17.6 mm (WxHxD) Weight: approx. 75 kgs Accessory: IR Remote Control	Backlight:	Direct-LED
Weight: approx. 75 kgs Accessory: IR Remote Control	Power Consumption:	360 Watt
Accessory: IR Remote Control	Outline Dimensions:	1410.4 × 828.4 × 17.6 mm (W×H×D)
	Weight:	approx. 75 kgs
Article Number: 17006	Accessory:	IR Remote Control
	Article Number:	17006

Alternative Panel Configuration: "Stripe" Mode



) DRAWING



eyevis Gmbl

ISOZERT

Hundsschleestrasse 23 • 72766 Reutlingen • Germany Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22

www.eyevis.de • info@eyevis.de

As at: 31.08.2013/V1.1 • Subject to change!

All trademarks and registered trademarks are the property of their respective owners. Copyright © 2013 eyevis GmbH. All rights reserved.